

PRODUCT DATA SHEET

BAGGES COOLING WATER HOSE-2

Temperature range: :	Intermittent Temperature -30°C + 500°C	Lining :	Non-conductive white EPDM Rubber
Reinforcement: :	High Tenacity Polyester Tyre Cord	Cover: :	Two opposing plies of heat resistant self-extinguishing black fiberlass directly over non-conductive white EPDM Rubber
Working pressure :	10 Bar @ 3:1 safety factor	Burst Pressure :	30 Bar

	Hose ID/OD	Wall Thickness	Length offered	Weight
ins	mm	mm	M	KG /M
1/2	13 / 25	6	60	0,62
3/4	19 / 32	6,5	60	0,81
1	25 /38	6,5	60	1,04
1 1/4	32 / 48	8	60	1,27
1 1/2	38 / 55	8,5	60	1,64
1 5/8	41 / 59	9	60	
1 3/4	45 / 63	9	60	2,11
1 7/8	48 / 65	8,5	60	2,2
2	50 / 68	9	60	2,23
2 1/2	63 / 81	9	60	2,67
* weight shown include hose tails & flange				
I.D		Inside diameter (or nominal bore size)		
O.D		Outside diamenter (approx) - tolerance may be invoked to suite customer needs for finntings etc.		
N.B all dimensions are nominal				

The information contained in this data sheet is believed to be true at the time of printing. Any statements contained or inferred to within are an expression of opinion and presented without guarantee. It is up to the user to determine suitability of use, or potential patent infringement for specific applications. This data sheet is believed to be true at the time of printing.

rev: 07/2025